

MIC2 EASY-PORT™ Microphone



DESCRIPTION

MIC2 is an operator console composed of a microphone on a flexible gooseneck mounted on a base and fitted with a button and indicator and an Easy-Port™ interface.

WHAT DOES EASY-PORT MEAN

An interface combining on the same cable the audio signal, power and control signals.

APPLICATIONS

In conjunction with SLICE 1154 amplifiers, XCHANGER codecs and XCHANGER.NET.HARD boards up to a maximum 50m working distance.

SPECIFICATIONS

Impedance	600 Ω balanced
Level	-8dBu max
Frequency response	60-10000Hz
Noise	<-95dBu, 22Hz-22kHz, "A"
THD (preamp only)	<1% 1kHz, -50dBu
Power	+5V 5mA max
Interface	Easy-Port™ on XLR
Control	Button/LED
Physical	190x140x370(WxDxH)mm
Operating Temperature	0-40°C

MIC2 V1.02 2004-01-10

Specifications may change without prior notice

Copyright © by Acutron 2001-2003 all rights reserved

LARSEN® is a trademark of Acutron Electroacustica

ABC-Abrunheira Business Center
Edifícios 10-11 R. das Macarocas
Abrunheira 2710-056 Sintra
Tel +351 219152040
Fax +351219154079
web: www.acutron.net
mail: info@acutron.net

DISTRIBUTOR



LARSEN®