



SAT-AT Selectors-Attenuators



DESCRIPTION

Designed for 100V systems, the SAT/AT selector/attenuator devices allow precise setting of the listening level in each zone or in the case of the SAT, also program selection.

FEATURES

- Metal housing for long life and optimal RF protection
- 6-program selector knob (SAT)
- 6-step step-type volume control (no potentiometers to wear out) with off position
- Optional plastic box for embedded or wall mounting application
- EN55103 compliant according to 89/336/EMC

SPECIFICATIONS

Frequency response	40Hz-15kHz \pm 3dB
Nominal power	
SAT/AT-6	6W
SAT/AT-12	12W
SAT/AT-30	30W
SAT/AT-60	60W
Input	100V on screw-type terminal posts
Attenuation steps	Off, 24, 18, 12, 6, 0 dB (Max)
Physical	120x120x65mm
Weight	
SAT6/AT6	400g
SAT/AT12	500g
SAT30/AT30	800g
SAT60/AT60	1Kg
Operating temperature	0-40°C

SAT-AT V1.11 2003-11-12
Specifications may change without prior notice
Copyright © by Acutron 2003 all rights reserved.
Larsen® is a trademark of Acutron Electroacustica.

ABC-Abrunheira Business Center
Edifícios 10-11 R. das Maçarocas
Abrunheira 2710-056 Sintra
Tel +351 219152040
Fax +351219154079
web: www.acutron.net
mail: info@acutron.net

DISTRIBUTOR



LARSEN®