

## XCHANGER.NET.HARD PCI Professional Audio Board



### DESCRIPTION

The XCHANGER.NET.HARD sound board is an AC'97 compliant PCI professional-quality sound board designed to work together with the XCHANGER.NET codec or LOGGER software.

### APPLICATIONS

- In large PA systems where computers are used to process audio.
- On any PC where high-quality audio is sought.

### FEATURES

- Balanced analog I/O
- Fully RF filtered
- EASY-PORT™ compatible phantom power for MIC2 microphone terminals
- Headphone monitoring output may be fitted as an optional extra (/H version)
- 4 inputs and 1 output, dual-channel
- 48kHz sample rate for 18-bit resolution A-D, D-A conversion, 8-48kHz using a built-in sample rate converter
- Fully EN55103 compliant according to 89/336/EMC when installed on a properly designed system
- Compatibility verified with Windows™ 98/2000/XP. Works under NT with a compatible driver not fully suited to the board.

### SPECIFICATIONS

BUS	PCI
Reference Level	0dBu (-10dBFS)
Input Impedance	12kΩ balanced
Output Impedance	100Ω balanced
Frequency response	20-20kHz ±1dB (Line) 50-15kHz ±±1/-3dB (MIC)
Input clipping point:	+10dBu (LINE), -24dBu (MIC)
Output clipping point:	+15dBu
THD+N	<0.01% 1kHz +10dBu (LINE) <0.15% 1kHz +10dBu (MIC)
Inp. Referenced Noise	IEC-A <-107dBu (MIC) <-75dBu (LINE)
Gain	52dB (MIC), 12dB (LINE)
Crosstalk	>60dB(1kHz) >40dB(20Hz-15kHz)
MRR	>40dB(1kHz-15kHz) >25dB at 20Hz,
Physical	1 PCI slot
Weight	150 g
Power supply	PC-supplied ±12V, +5V
Operating temp.	0-40°C

XCHANGER.NET.HARD V1.03 2003-11-19  
Specifications may change without prior notice  
Copyright © by Acutron 2002-2003 all rights reserved.  
Acutron® is a trademark of Acutron Electroacustica.  
Windows is a trademark of Microsoft Corp.

**ABC-Abrunheira Business Center**  
**Edifícios 10-11 R. das Maçarocas**  
**Abrunheira 2710-056 Sintra**  
**Tel +351 219152040**  
**Fax +351219154079**  
**web: www.acutron.net**  
**mail: info@autron.net**

### DISTRIBUTOR



# Acutron



## digital audio